



EM-P90115-SR-915

902-928 MHz, 2 dBi Gain

MESH Portable Antenna

- » Provides 902-928 MHz Full Coverage for ISM Band
- » Aesthetic, Low Profile Form Factor
- » Flexible, Rugged, PU/TPE Weatherproof Molded Construction
- » Swivel 0° & 90° Mounting Orientation
- » Type-N Direct Radio Connector Attachment
- » Weather Protected Outdoor & Indoor MESH Applications

Electrical Specifications

Frequency Band	902-928 MHz
VSWR	< 2:1
Impedance	50Ω
Gain	2.0 dBi
Pattern Coverage	Omnidirectional
Polarization	Vertical, Linear
Antenna Type	Half Wave

Mechanical Specifications

Color / Material	Black / ABS
Length x Width (Mounted @ 90°)	5.40 in. (137) x 0.24 in. (6.0) whip .39 in. (10.0) base. @ 90° 4.4 in.(111)
Mounting Application	Direct Connector Attachment
Weight	1.5 oz. (42g)
Mounting Orientations	Swivel 0° to 90°
Connector	SMA RP
Environment	Weather Protected Outdoor & Indoor
Operating Temperature	-20° C to 65° C
Storage Temperature	-30° C to 70° C

Specifications subject to change without notification.

ELECTRO-MAGWAVE, INC.

10221 Sweet Valley Drive, STE 1 Valley View, OH 44125 † 216-453-1160 ‡ 216-447-8828 www.emwaveinc.com