



RFFT-12SM-001-50M

Bend Insensitive Singlemode Fiber DLC to DLC 12-Fiber Cable Assembly with pulling grip, 50 m

Construction Materials

Fiber Type	Bend insensitive singlemode fiber (G.657.A2)
Total Fibers, quantity	12
Furcation Color	Yellow
Jacket Color	Black

Dimensions

Cord Length	50.00 m 164.04 ft
Breakout Length, Fiber, end 1	1 m 3 ft
Breakout Length, Fiber, end 2	2 m 7 ft

Environmental Specifications

Environmental Space	Low Smoke Zero Halogen (LSZH)
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Construction Type	Discrete fiber trunk
Cable Glands	No glands
Color, connector A	Blue
Color, connector B	Blue
Interface Body Style, connector A	Straight
Interface Body Style, connector B	Straight
Interface Feature, connector A	Uniboot
Interface Feature, connector B	Uniboot
Interface, connector A	DLC
Interface, connector B	DLC
Minimum Bend Radius, furcation	30.0 mm 1.2 in
Pulling Grips, quantity	1

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



Included Products

8106092/DB | R-012-CN-8W-F12BK — Single Jacket All-Dielectric Indoor/Outdoor Cable, 1 –24 fiber Arid Core

RFFT-12SM-001-50M

construction, central loose tube

- DB-8W-LT (Product Component—not orderable) — LightScope ZWP® Singlemode Fiber